## **BRINGHELI**

FRAMES TOOLS & JIGS 8040 WEST PLEASANT VALLEY RD. PARMA, OHIO 44130 440 568-0407

## **DEDACCIAI Steel Tubing** price list 2015

| 71                        |                                | , ,          |                  |                  | 71   | TDA       | UNC          |              | - 10        |             |
|---------------------------|--------------------------------|--------------|------------------|------------------|------|-----------|--------------|--------------|-------------|-------------|
| ZERO Heat Treated 1-5     |                                |              | 6-10             |                  | _    |           | _            | 6-10         |             |             |
| TT                        | 28.6 65/4/65                   | 600          | \$36             | \$35             | TT   | 25.4      | 8/5/8        | 600          | \$20        | \$19        |
| TT                        | 31.7 65/45/65                  | <b>590</b>   | \$36             | \$35             | TT   | 28.6      | 8/5/8        | 600          | \$20        | \$19        |
| TT                        | LOW TORSION P                  | ROF.         | \$40             | \$39             | TT   | 31.7      | 8/5/8        | 600          | \$20        | \$19        |
| DT                        | 31.7 65/45/65                  | 635          | \$38             | \$37             | DT   | 28.6      | 8/5/8        | 650          | \$21        | \$20        |
| DT                        | 35 65/5/65                     | 650          | \$39             | \$37             | DT   | 31.7      | 8/5/8        | 650          | \$21        | <b>\$20</b> |
| DT                        | 38 75/45/7                     | 650          | <b>\$40</b>      | \$39             |      |           | 0.17.10      |              |             |             |
| DT                        | 31.7bb to 28.6                 | 610          | \$40             | \$39             | DT   | 33        | 8/5/8        | 650          | \$22        | \$21        |
| DT                        | 35bb to 31.7dt                 | 650          | \$42             | <b>\$41</b>      | DT   | 35        | 8/5/8        | 650          | \$23        | \$22        |
| DT LOW TORSION PROF. \$42 |                                |              | \$41             | DT               | 35bb | to 31.7ht | 650          | \$26         | \$25        |             |
| ST                        | 28.6 8/6                       | 620          | \$36             | \$35             | ST   | 28.6      | 8/6          | 650          | \$20        | \$19        |
| ST                        | 35 w/sleeve 31.6               | 628          | \$40             | \$39             | ST   |           | ex bt 1.1/6/ |              | \$20        | \$19        |
|                           |                                |              |                  |                  | ST   | 31.7      | w/sleeve 2   | 7.2 650      | <b>\$26</b> | \$25        |
| CS                        | <b>26/17</b> .55               | 410          | \$45pr           | \$44pr           | ~~   | 2011      | 0.15         |              |             |             |
| CS                        | 29. 9/16 7/45                  | 410          | \$48pr           | \$47pr           | CS   | 30/16     | 8/6          | 425          | \$30pr      | \$28pr      |
|                           |                                |              |                  |                  | CS   | 30/16     | 1.0/7        | 450          | \$30pr      | \$28pr      |
| SS<br>SS                  | 18//12.5<br>14/18/12.5 Biconic | 560<br>o 560 | \$26pr<br>\$28pr | \$25pr<br>\$27pr | CS   | 24 rou    | nd 8/6       | 425          | \$30pr      | \$28pr      |
|                           |                                |              | · - I            | · r              | SS   | 14/10.5   | .6           | 560          | \$21pr      | \$20pr      |
|                           |                                |              |                  |                  | SS   | 14/12     | .6           | 560          | \$21pr      | \$20pr      |
| 71                        | DOLINO 20                      | ) orac       |                  |                  | SS   | 16/10.5   | .6           | 560          | \$21pr      | \$20pr      |
|                           | EROUNO 29                      | ers)         | 1-5              | 6-10             | SS   | 16/12.5   | .6           | 560          | \$21pr      | \$20pr      |
| TT                        | 31.7 8/5/8                     | 650          | \$21             | \$20             | SS   | 16/10.5   | Biconico     | 560          | \$23pr      | \$22pr      |
| DT                        | 38 8/5/8                       | 750          | \$25             | <b>\$24</b>      | SS   | 16/12.5   | double b     | end CC       | \$28pr      | \$27pr      |
| ST                        | 31.7 w/sleeve 27.2 9/6         | /9 EB (      | 630 \$25         | <b>\$24</b>      | SS   | 19/12.5   | .7           | 560          | \$21pr      | \$20pr      |
| CS                        | 30/16 1/.7 DB                  | 440          | \$30             | <b>\$29</b>      |      |           |              |              |             |             |
| SS                        | 19/12.5 DB .7                  | 560          | \$28             | <b>\$27</b>      |      |           |              |              |             |             |
|                           |                                |              |                  |                  | HT   | 31.7      | 1            | 200          | \$10        | <b>\$9</b>  |
|                           |                                |              |                  |                  | HT   | 31.7      | 1            | 650          | \$17        | \$16        |
| ZERO DUE 25CrM04 SEAMLESS |                                |              |                  |                  | HT   | 32.5      | 1.3          | 200          | \$11        | \$10        |
|                           |                                |              |                  | HT               | 32.5 | 1.3       | 650          | \$19         | \$18        |             |
| CS                        | 29.9/16 Single bend            | 425          | <b>\$26pr</b>    | \$25pr           | HT   | 36.5      | 1.3          | 200          | \$11        | \$10        |
| CS                        | 29.9/16 Double bend            | 425          | \$30pr           | \$29pr           | HT   | 36.5      | 1.3          | 650          | \$19        | \$18        |
| CS                        | 22.2 R.O.R7                    | 425          | \$26pr           | \$25pr           | HT   | 1.5"      | to 1.125"    | 220 w/ c     | eup \$65    |             |
|                           | 19/12.5 single bend            | 560          | \$26pr           | \$25pr           | SC   | 25.4      | 2.3/1.55     |              | \$16        | \$15        |
| SS 1                      | 19/12.5 double bend            | 560          | \$28pr           | \$27pr           | SC   | 28.6      | 2.3/1.55     |              | \$16        | \$15        |
|                           |                                |              |                  |                  | SC   | 25.4      | 200/220/2    | 240/260 thre | aded \$17   | \$16        |
| FB                        | 28/19 1/.7                     | 430          | \$25pr           | <b>\$24pr</b>    |      |           |              |              |             |             |
| FB                        | 24round 1/.7                   | 430          | \$25pr           | \$24pr           |      |           |              |              |             |             |